



RSSTM LPS

- patented -
PANEL FASTENER



Star drive #25 applies approximately 450 lbs torque energy.

patented washer type head reinforced shoulder Extremely strong, patented, low profile, washer type head, provides superior hold down pressure to panel.

case hardened steel CLIMATEKTM coating, ACQ Approved. Lifetime limited warranty.

No pre-drilling is required.
 Easy, fast installation in one operation.
 720 lbs of shear strength.

1/4" x 3" threads Very sharp deep rolled threads, provide fast and easy one step installation. Also, extreme pulling and withdrawal power. Complete and easy removal, without damage to material.

patented W-CutTM Slices groove for next thread, reducing tension and pressure on fastener, providing ease of installation.

Zip-Tip For quick and easy starting.

BULK

UPC Code	Metric	U.S. Standard (Nominal Size)	Approx pcs /box	INVOICE \$/100	\$/box	Approx pcs/lb	Approx \$/lb
772691 91175 9	6.0 x 150	1/4 x 6"	500	96.68	483.40	24	23.20
772691 91181 0	6.0 x 200	1/4 x 8"	500	121.74	608.70	19	23.13
772691 91184 1	6.0 x 230	1/4 x 9"	500	140.87	704.35	16	22.54
772691 91187 2	6.0 x 250	1/4 x 10"	500	164.71	823.55	15	24.71
772691 91190 2	6.0 x 275	1/4 x 11"	500	176.09	880.45	17	29.94
772691 91193 3	6.0 x 300	1/4 x 12"	500	201.71	1,008.55	12	24.21
772691 91200 8	6.0 x 355	1/4 x 14"	300	213.65	640.95	11	23.50

HANDY-PAK

UPC Code	Metric	U.S. Standard (Nominal Size)	Pcs/box	\$/100	\$/box	Master Ctn Qty
772691 93175 7	6.0 x 150	1/4 x 6"	50	111.20	55.60	n/a
772691 93181 8	6.0 x 200	1/4 x 8"	50	140.02	70.01	n/a
772691 93184 9	6.0 x 230	1/4 x 9"	50	162.02	81.01	n/a
772691 93187 0	6.0 x 250	1/4 x 10"	50	189.42	94.71	n/a
772691 93190 0	6.0 x 275	1/4 x 11"	50	202.52	101.26	n/a
772691 93193 1	6.0 x 300	1/4 x 12"	50	231.98	115.99	n/a
772691 93200 6	6.0 x 355	1/4 x 14"	50	245.70	122.85	n/a

RSSTM LPS screw #1/4 take a #25 bit.